

3%

AFFF

AQUEOUS FILM FORMING FOAM CONCENTRATE

DESCRIPTION

PHOS-CHEK® 3% AFFF foam concentrate is proportioned at 3% concentration, compatible with fresh and sea water, for both fixed foam systems and manual application. PHOS-CHEK 3% AFFF foam is effective on hydrocarbon fuels like gasoline, heptane, crude oil, and other fuels that are not soluble in water. PHOS-CHEK foam concentrates are ideal for use on fixed foam systems in industrial facilities and is compatible with standard proportioning and foam making devices including bladder tank with proportioning devices, foam chambers, foam makers, sprinklers, self-inducting type nozzles, and in-line proportioners. PHOS-CHEK 3% AFFF is our systems level foam with our most extensive third party listings to address hydrocarbon fuel fires in industrial facilities. PHOS-CHEK 3% AFFF is also an excellent choice for manual firefighting operations including monitor and hand-line applications.

APPLICATIONS

PHOS-CHEK 3% AFFF may be used with low expansion foam equipment (nozzles and monitors), non-aspirating devices (water spray nozzles and standard sprinklers) and medium expansion foam devices to fight fires involving Class B hydrocarbon fuel fires such as aviation fuels, hydraulic oil, and diesel fuels. It is not suitable for use on polar solvents or water miscible fuels such as alcohols, ketones, esters, and ethers.

APPROVAL CERTIFICATIONS

UL 162 Listed and EN 1568-3:2008 (Class IB) Approved. This concentrate is only FM Approved in conjunction with the specific proportioning and discharge devices as shown in the Approval Guide (www.ApprovalGuide.com).

SHELF LIFE, INSPECTION AND TESTING

The shelf life of any foam concentrate is maximized by proper storage conditions and maintenance. Factors affecting shelf life are wide temperature fluctuation, evaporation, dilution, and contamination by foreign materials. Properly stored PHOS-CHEK Class B AFFF foam concentrates should have no significant loss of firefighting performance for 20+ years. However, the National Fire Protection Association (NFPA) recommends annual testing of all firefighting foams.



TYPICAL PHYSICAL PROPERTIES [at 77 °F (25 °C)]

Appearance	Clear, light yellow liquid
Specific Gravity	1.000 – 1.040
pH	8.0 + 0.5
Viscosity (LV-1 Spindle @ 60 RPM)*	6 ± 4 cP
Refractive Index	1.3600 – 1.3700
Lowest Temperature for Use	32 °F (0 °C)
Freezing Point	21 °F (-6 °C)

*Brookfield LVT

VISCOSITY

@ 35 °F (1.7 °C)	LV-2 Spindle @ 60 RPM*	11 ± 9 cP
@ 68 °F (20 °C)	LV-1 Spindle @ 60 RPM*	6 ± 4 cP

*Brookfield LVT

For more information, contact any of our worldwide Perimeter Solutions Fire Safety offices or visit www.Phos-Chek.com or www.Perimeter-Solutions.com

UNITED STATES
PERIMETER SOLUTIONS, LP
10667 Jersey Blvd.
Rancho Cucamonga, CA 91730
Tel: +1 800 682 3626
+1 909 983 0772
24HR: +1 909 946 7371

EMEA
PERIMETER SOLUTIONS, LP
Polígono Industrial De Baiña, Parc, 23
33682 Baiña-Mieres Asturias – Spain
Tel: +34 985 242945
24HR: +44 01202864796

ASIA PACIFIC
PERIMETER SOLUTIONS, LP
3 Charles Street
St Marys NSW 0276 – Australia
Tel: +61 2 9673 5300
24HR: +61 2 9430 6396

3%

AFFF

AQUEOUS FILM FORMING FOAM CONCENTRATE

STORAGE AND HANDLING

The concentrate should be stored at temperatures between 35 °F (1.7 °C) and 120 °F (49 °C)**, in the original containers, approved bladder tanks, stainless steel, high density polyethylene, fiberglass or epoxy lined tanks. Concentrate piping acceptable materials of construction include stainless steel (either 304 or 316), some plastic piping including fiberglass and PVC, red brass, and black iron as long as the system is completely flooded eliminating the air/foam concentrate/carbon steel interface. Avoid permanent contact with carbon steel, iron, some copper alloys, & aluminum when the piping material and concentrate will be exposed to air. Galvanized piping should not be used in direct contact with the foam concentrate.

Foam concentrates are subject to evaporation, which accelerates when the product is exposed to air. Storage tanks should be sealed and fitted with a pressure vacuum vent to prevent free exchange of air.

**EN APPROVAL: 35 °F (1.7 °C) and 122 °F (50 °C)

HANDLING PRECAUTIONS

- For DETAILED SAFETY INFORMATION, please refer to the SDS.
- **Precautionary Measures:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary contact and removal of the material from the eyes, skin and clothing.
- **Eye Protection:** As a good industrial practice, the use of chemical goggles is recommended.
- **If in the eyes:** Flush with plenty of water.
- **Skin Protection:** Wear protective gloves when handling concentrate to minimize skin contact. Wash hands and contaminated skin after handling.
- **Respiratory Protection:** None required.
- For complete SDS, visit www.phos-chek.com

PACKAGING

ORDERING INFORMATION

	lb*	kg*	PART #
5 gallon pail (20 litres), PHOS-CHEK 3% AFFF	43	19	10003964
55 gallon drum (200 litres), PHOS-CHEK 3% AFFF	468	212	10003963
265 gallon tote (1,000 litres), PHOS-CHEK 3% AFFF	2255	1023	10003962

*Approximate shipping weight

Contact your local authorized PHOS-CHEK distributor or factory sales representative for details <https://phoschek.com/contact/>

