

# LC95



## (LC95A-R, LC95A-FX, LC95A-MV, LC95W) LONG-TERM FIRE RETARDANT

LOW/MEDIUM VISCOSITY LIQUID CONCENTRATE

### DESCRIPTION

Phos-Chek® LC95 fire retardants are concentrated liquids that mix readily with water by recirculation, agitation or with mechanical or electronic Phos-Chek liquid proportioning systems. Phos-Chek LC95 fire retardant solutions are the only liquid concentrate (LC) ammonium polyphosphate retardants that offer both the ease of mixing and handling of a liquid and the aerial drop advantages of a gum-thickened retardant. The elastic nature of the thickener in Phos-Chek retardants reduces drift, dispersion and evaporation and facilitates increased fuel coverage, wrap around and penetration through canopy and ladder fuels to ground vegetation. Recovery can exceed 90%.

Phos-Chek LC95 is available in red iron oxide (R), fugitive (F) color, and uncolored (W). The fugitive color maintains visibility during application, but slowly fades after exposure to sunlight. LC95A-R is available as low viscosity or medium viscosity. Medium viscosity is ideal for higher altitude drops or where higher coverage levels are desired.



### PACKAGING

Phos-Chek LC95 is available in bulk trucks, 260 gal. totes, 30 and 55 gal. drums and 5 gal. pails. Special package sizes available.

### PRODUCT CHARACTERISTICS

Color	Red (R), Fugitive (MV), Uncolored (W)
Mix Ratio	5.5 gal. of water/gal. concentrate
Yield	1054 gal./ton of concentrate, 4398 liters/metric ton of concentrate
Concentrate Density	12.29 lbs./gal., 1,476 kg/liter
Solution Density	8.97 lbs./gal. of mixed retardant, 1.077 kg./liter
Viscosity	100-400 centipoise (cP)
Refractometer	12.75-14.50

APPLICATION	Long-Term Retardant	Gel	Class A Foam	Water
Indirect Attack	✓✓✓✓	✓✓	✓	
Direct/Parallel Attack	✓✓✓✓	✓✓✓	✓✓	✓
Interior Structure Attack		✓✓	✓✓✓✓	✓
Structure Protection-Indirect Application	✓✓✓✓	✓✓✓	✓✓	✓
Structure Protection-Direct Application		✓✓✓✓	✓✓✓	✓
Mop Up	✓✓	✓✓	✓✓✓✓	✓
Prescribed Burn Control	✓✓✓✓	✓✓✓	✓✓	✓

✓✓✓✓ = Superior Effectiveness

✓✓ = Good Effectiveness

✓✓✓ = Excellent Effectiveness

✓ = Baseline Effectiveness

For more information,  
contact any of our worldwide  
Perimeter Solutions Fire  
Safety offices or visit us  
at [Phos-Chek.com](http://Phos-Chek.com) or  
[Perimeter-Solutions.com](http://Perimeter-Solutions.com)

#### United States

Perimeter Solutions  
10667 Jersey Blvd.  
Rancho Cucamonga,  
CA 91730  
Tel: (800) 682-3626  
(909) 983-0772  
24 Hrs: (909) 946-7371  
Fax: (909) 984-4770

#### Canada

Perimeter Solutions  
Canada LTD  
3060 Airport Road  
Kamloops, BC  
Canada, V2B 7X2  
Tel: (800) 682-3626  
(909) 983-0772  
24 Hrs: (909) 946-7371  
Fax: (909) 984-4770

#### Europe

Biogema, a Perimeter  
Solutions Company  
415, rue Armand-Pole  
d'Activities  
F-13852 Aix-en-Provence  
Cedex 3 France  
Tel: +33(0) 4 42 24 45 08  
Fax: +33(0) 4 42 24 29 9

#### Australia

Perimeter Solutions  
46 Hudson Crescent  
Albury New South Wales  
2641 Australia  
Tel: +61 2 6040 6900  
Fax: +61 2 6040 5001

#### Latin America

Perimeter Solutions  
Chile Ltda.  
Las Brisas 2271, lote A.  
Concepción, Chile.  
Tel: +56 41 412321722  
Tel: +56 9 62338737  
Fax: +56 9 71370977

# LC95



## (LC95A-R, LC95A-FX, LC95A-MV, LC95W) LONG-TERM FIRE RETARDANT

LOW/MEDIUM VISCOSITY LIQUID CONCENTRATE



### USES

Phos-Chek LC95A-R fire retardants are qualified by the USDA Forest Service under specification 5100-304c for use in fixed-wing air tankers and helicopters with buckets and ground engines. LC95A-R is ideal for use in multi-engine, fixed-wing air tankers and single-engine air-tankers (SEATS). The concentrate is delivered to the using location as a low viscosity liquid and is stored in the concentrate form. It is diluted and mixed with water as it is transferred to the delivery system. LC95A-R and LC95A-MV are colored to provide effective aerial application. LC95A-Fx provides ultra-high visibility when dropped, but slowly fades after exposure to sunlight.

Uncolored Phos-Chek LC95W is ideal for ground application where color is not required or is undesirable.

Phos-Chek fire retardants are used for wildland fire control in forest, brush or grassland. Functionally, Phos-Chek retardants react with and alter the thermal decomposition of wildland fuels so that they do not support flaming or glowing combustion. This deprives the fire of fuel, reducing fire intensity and the rate of flame spread. They are useful as well in prescribed burning. When applied at low application rates, fire intensity is dramatically decreased while slow burning is allowed.

### HANDLING PRECAUTIONS

- FOR DETAILED SAFETY INFORMATION, please refer to the SDS.
- Minimally irritating to eyes; non-irritating to skin.
- If in eyes: Flush with plenty of water.
- Precautionary Measures: Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary contact and removal of the material from the eyes, skin and clothing.
- Eye Protection: As a good industrial practice, the use of chemical goggles is recommended. Eye flushing equipment should also be available.
- Skin Protection: As a good industrial practice, wear protective gloves to minimize skin contact. Wash hands and contaminated skin after handling.
- Respiratory Protection: Wear dust mask if dusty conditions exist. Avoid breathing vapor or mist.
- For complete SDS, visit [www.phos-chek.com](http://www.phos-chek.com)

### NOTICE

Although the information and recommendations set forth herein (hereinafter "information") are presented in good faith and believed to be correct as of the date hereof, Perimeter Solutions LP and its affiliates makes no representations or warranties as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will Perimeter Solutions LP be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information or the product to which the information refers. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment or formulation in conflict with any patent, and Perimeter Solutions LP makes no representation or warranty, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

© 2018 Perimeter Solutions LP. All rights reserved.