

MVP-FX



LONG-TERM FIRE RETARDANT

HIGH VISIBILITY MV POWDER CONCENTRATE



DESCRIPTION

Phos-Chek® MVP-Fx is an ultra high visibility powder concentrate that mixes readily with water by recirculation, agitation or Phos-Chek eductor-mixing systems. MVP-Fx is a highly visible, fugitive color retardant that provides superior visibility in the air and on the ground when applied, but slowly fades during exposure to sunlight.

Phos-Chek MVP-Fx is a gum-thickened, medium viscosity retardant that provides highly effective and accurate aerial drops from all airtankers. The elastic nature of Phos-Chek MVP-Fx solution improves aerial delivery performance by reducing drift, dispersion, and evaporation, and facilitates increased fuel coverage, wrap around and penetration through canopy and ladder fuels to ground vegetation. Recovery can exceed 90%. It is ideal for use in multi-engine airtankers, Very Large Air Tankers (VLATs) and Single Engine Air Tankers (SEATS), and can be accurately dropped at higher drop heights.

PACKAGING

Phos-Chek MVP-Fx is available in 2000 lbs. Phos-Bin containers, 2000 lbs. bulk bags, and 50 lbs. pails. Special package sizes available.

PRODUCT CHARACTERISTICS

Color	Fugitive (F)
Mix Ratio	0.96 lbs./gal. of water, 0.11 kg per liter
Yield	2209 gal. per ton of concentrate, 9189 liters/1000 kilograms
Solution Density	8.75 lbs. per gallon, 1.05 kilograms/liter
Viscosity	401-800 centipoise (cP) specification, 401-600 cP Typical
Refractometer	8.0-9.75

APPLICATION

	Long-Term Retardant	Gel	Class A Foam	Water
Indirect Attack	✓✓✓✓	✓✓	✓	
Direct/Parallel Attack	✓✓✓✓	✓✓✓	✓✓	✓
Interior Structure Attack		✓✓	✓✓✓✓	✓
Structure Protection-Indirect Application	✓✓✓✓	✓✓✓	✓✓	✓
Structure Protection-Direct Application		✓✓✓✓	✓✓✓	✓
Mop Up	✓✓	✓✓	✓✓✓✓	✓
Prescribed Burn Control	✓✓✓✓	✓✓✓	✓✓	✓

✓✓✓✓ = Superior Effectiveness
 ✓✓✓ = Excellent Effectiveness

✓✓ = Good Effectiveness
 ✓ = Baseline Effectiveness

For more information, contact any of our worldwide Perimeter Solutions Fire Safety offices or visit us at Phos-Chek.com or Perimeter-Solutions.com

United States
 Perimeter Solutions
 10667 Jersey Blvd.
 Rancho Cucamonga, CA 91730
 Tel: (800) 682-3626
 (909) 983-0772
 24 Hrs: (909) 946-7371
 Fax: (909) 984-4770

Canada
 Perimeter Solutions
 Canada LTD
 3060 Airport Road
 Kamloops, BC
 Canada, V2B 7X2
 Tel: (800) 682-3626
 (909) 983-0772
 24 Hrs: (909) 946-7371
 Fax: (909) 984-4770

Europe
 Biogema, a Perimeter
 Solutions Company
 415, rue Armand-Pole
 d'Activites
 F-13852 Aix-en-Provence
 Cedex 3 France
 Tel: +33(0) 4 42 24 45 08
 Fax: +33(0) 4 42 24 29 9

Australia
 Perimeter Solutions
 46 Hudson Crescent
 Albury New South Wales
 2641 Australia
 Tel: +61 2 6040 6900
 Fax: +61 2 6040 5001

Latin America
 Perimeter Solutions
 Chile Ltda.
 Las Brisas 2271, lote A.
 Concepción, Chile.
 Tel: +56 41 412321722
 Tel: +56 9 62338737
 Fax: +56 9 71370977

MVP-FX



LONG-TERM FIRE RETARDANT

HIGH VISIBILITY MV POWDER CONCENTRATE



USES

Phos-Chek MVP-Fx long-term retardant is qualified by the USDA Forest Service under specification 5100-304c for use in fixed wing air tankers and helicopters with buckets. MVP-F is an all-phosphate, gum thickened, fugitive colored retardant. It is a highly effective long-term retardant with a higher yield than any other retardant on the market.

Phos-Chek long-term fire retardants are used for wildland fire control in forest, brush or grassland. Functionally, Phos-Chek retardants react with, and alter the decomposition of wildland fuels, so that when used at the qualified mix ratio they do not support flaming or glowing combustion. This deprives the fire of fuel, reducing fire intensity and rate of spread. Long-term retardants are useful in prescribed burning. When applied at low application rates, fire intensity can be dramatically decreased while slow burning continues.

HANDLING PRECAUTIONS

- FOR DETAILED SAFETY INFORMATION, please refer to the SDS.
- Minimally irritating to the eyes, non-irritating to skin.
- Eye Protection: As a good industrial practice, the use of chemical goggles is recommended.
- Precautionary Measures: Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary contact and removal of the material from the eyes, skin and clothing.
- If in eyes: Flush with plenty of water.
- Skin Protection: As a good industrial practice, wear protective gloves to minimize skin contact. Wash hands and exposed skin after handling.
- Respiratory Protection: Avoid breathing dust. Respiratory protection should be worn when airborne exposure is excessive. See SDS for further guidance.
- For complete SDS, visit www.phos-chek.com

NOTICE

Although the information and recommendations set forth herein (hereinafter "information") are presented in good faith and believed to be correct as of the date hereof, Perimeter Solutions LP and its affiliates makes no representations or warranties as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will Perimeter Solutions LP be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information or the product to which the information refers. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment or formulation in conflict with any patent, and Perimeter Solutions LP makes no representation or warranty, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

© 2018 Perimeter Solutions LP. All rights reserved.