

# LC95



## LONG-TERM FIRE RETARDANT

### LOW/MEDIUM VISCOSITY LIQUID CONCENTRATE (LC95A-R, LC95A-Fx, LC95W)

#### DESCRIPTION

PHOS-CHEK® LC95 fire retardants are concentrated liquids that mix readily with water by recirculation, agitation or with mechanical or electronic PHOS-CHEK liquid proportioning systems. PHOS-CHEK LC95 fire retardant and variants are the only liquid concentrate (LC) ammonium polyphosphate retardants that offer both the ease of mixing and handling of a liquid and the aerial drop advantages of a gum-thickened retardant. The elastic nature of the thickener in PHOS-CHEK retardants reduces drift, dispersion and evaporation and facilitates increased fuel coverage, wrap around and penetration through canopy and ladder fuels to ground vegetation. Recovery can exceed 90%.

PHOS-CHEK LC95 is available in Red Iron Oxide (R), Fugitive (F) and Uncolored (W). The fugitive color maintains visibility during application, but slowly fades after exposure to sunlight. LC95A-R is available as low viscosity or medium viscosity. Medium viscosity is ideal for higher altitude drops or where higher coverage levels are desired.

#### APPLICATIONS

PHOS-CHEK LC95A-R fire retardants are qualified by the USDA Forest Service under specification 5100-304c for use in fixed-wing air tankers, helicopters with buckets and ground engines. LC95A-R is ideal for use in multi-engine, fixed-wing air tankers and single-engine air-tankers. The concentrate is delivered to the using location as a low or medium viscosity liquid and is stored in the concentrate form. It is diluted and mixed with water as it is transferred to the delivery system. LC95A-R and LC95A-Fx are colored to provide effective aerial application. LC95A-Fx provides ultra-high visibility when dropped. Both retardants fade after exposure to sunlight.

Uncolored PHOS-CHEK LC95W is ideal for ground application where color is not required or is undesirable.

PHOS-CHEK fire retardants are used for wildland fire control in forest, brush or grassland. Functionally, PHOS-CHEK retardants react with and alter the thermal decomposition of wildland fuels so that they do not support flaming or glowing combustion. This deprives the fire of fuel, reducing fire intensity and the rate of flame spread. LC95 fire retardant is also useful for prescribed burns. When applied at low application rates, fire intensity is dramatically decreased while slow burning is allowed.



APPLICATION	Long-Term Retardant	Gel	Class A Foam	Water
Indirect Attack	✓✓✓✓	✓✓	✓	
Direct/Parallel Attack	✓✓✓✓	✓✓✓	✓✓	✓
Interior Structure Attack		✓✓	✓✓✓✓	✓
Structure Protection-Indirect Application	✓✓✓✓	✓✓✓	✓✓	✓
Structure Protection-Direct Application		✓✓✓✓	✓✓✓	✓
Mop Up	✓✓	✓✓	✓✓✓✓	✓
Prescribed Burn Control	✓✓✓✓	✓✓✓	✓✓	✓

✓✓✓✓ = Superior Effectiveness

✓✓✓ = Excellent Effectiveness

✓✓ = Good Effectiveness

✓ = Baseline Effectiveness

For more information, contact any of our worldwide Perimeter Solutions Fire Safety offices, see back page for locations, or visit [www.Phos-Chek.com](http://www.Phos-Chek.com) or [www.Perimeter-Solutions.com](http://www.Perimeter-Solutions.com)

# LC95

## LONG-TERM FIRE RETARDANT LOW/MEDIUM VISCOSITY LIQUID CONCENTRATE (LC95A-R, LC95A-Fx, LC95W)



### PRODUCT CHARACTERISTICS

Color	Red (R), Fugitive (F), Uncolored (W)
Mix Ratio	5.5 gal. of water/gal. concentrate
Yield	1054 gal./ton of concentrate, 4398 litres/metric ton of concentrate
Concentrate Density	12.29 lbs./gal., 1,476 kg./litre
Solution Density	8.97 lbs./gal. of mixed retardant, 1.077 kg./litre
Viscosity	100 – 400 centipoise (cP)
Refractive Index	12.75 – 14.50

### HANDLING PRECAUTIONS

- FOR DETAILED SAFETY INFORMATION, please refer to the SDS.
- Minimally irritating to eyes; non-irritating to skin.
- If in eyes: Flush with plenty of water.
- **Precautionary Measures:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary contact and removal of the material from the eyes, skin and clothing.
- **Eye Protection:** As a good industrial practice, the use of chemical goggles is recommended. Eye flushing equipment should also be available.
- **Skin Protection:** As a good industrial practice, wear protective gloves to minimize skin contact. Wash hands and contaminated skin after handling.
- **Respiratory Protection:** Wear dust mask if dusty conditions exist. Avoid breathing vapor or mist.
- For complete SDS, visit [www.phos-chek.com](http://www.phos-chek.com)

## PACKAGING

### ORDERING INFORMATION

	lbs*	kgs*	PART #
5 gallon pail (20 litres), PHOS-CHEK LC95A-R Retardant	43	19	10003939
55 gallon drum (200 litres), PHOS-CHEK LC95A-R Retardant	490	222	10002792
260 gallon tote (984 litres), PHOS-CHEK LC95A-R Retardant	2340	1061	10003222
Bulk, PHOS-CHEK LC95A-R Retardant	—	—	10001554
<hr/>			
5 gallon pail (20 litres), PHOS-CHEK LC95A-Fx Retardant	43	19	10004605
55 gallon drum (200 litres), PHOS-CHEK LC95A-Fx Retardant	490	222	10004842
260 gallon tote (984 litres), PHOS-CHEK LC95A-Fx Retardant	2340	1061	10004595
Bulk, PHOS-CHEK LC95A-Fx Retardant	—	—	10004642
<hr/>			
5 gallon pail (20 litres), PHOS-CHEK LC95W Retardant	43	19	10002983
55 gallon drum (200 litres), PHOS-CHEK LC95W Retardant	490	222	10004780
260 gallon tote (984 litres), PHOS-CHEK LC95W Retardant	2340	1061	10003107
Bulk, PHOS-CHEK LC95W Retardant	—	—	10002883

\*Approximate shipping weight

Contact your local authorized PHOS-CHEK distributor or factory sales representative for additional details

<https://phoschek.com/contact/>



---

**UNITED STATES**

PERIMETER SOLUTIONS, LP  
10667 Jersey Blvd.  
Rancho Cucamonga, CA 91730  
Tel: +1 800 682 3626  
+1 909 983 0772  
24HR: +1 909 946 7371

**CANADA**

PERIMETER SOLUTIONS CANADA, LTD  
3060 Airport Road  
Kamloops, BC V2B 7X2  
Canada  
Tel: +1 250 544 3530  
24HR: +1 800 665 2535

**EUROPE**

PERIMETER SOLUTIONS BIOGEMA SAS  
415, rue Louis Armand  
Pôle d'activités Aix les Milles  
F-13290 Aix en Provence France  
Tel: +33 4 42 24 45 08  
24HR: +33 6 8910 3300

**AUSTRALIA**

PHOS-CHEK AUSTRALIA  
46 Hudson Crescent  
Albury NSW 2641  
Australia  
Tel: +61 2 6040 6900  
24HR: +61 0 417 525 970

PERIMETER SOLUTIONS, LP  
AIRBASE SERVICE CENTER  
5980 E Commerce Loop  
Post Falls, ID 83854  
Tel: +1 208 765 8380  
24HR: +1 208 765 8380

PERIMETER SOLUTIONS CANADA, LTD  
110-55202 SH 825  
Sturgeon County, AB T8L 5C1  
Canada  
Tel: +1 780 992 7900  
24HR: +1 780 992 7900

**LATIN AMERICA**

PHOS-CHEK CHILE LTDA  
Las Brisas 2271, Lote A  
Palomares Concepción Chile  
Tel: +56 2 3269 3100  
Tel: +56 9 6233 8737

**For more information, contact  
any of our worldwide Perimeter  
Solutions Fire Safety offices or  
visit [www.Phos-Chek.com](http://www.Phos-Chek.com) or  
[www.Perimeter-Solutions.com](http://www.Perimeter-Solutions.com)**